Tape 2 AC

Double-faced acrylic adhesive tape

Riwega | eternitycomfort

Rev.05

Technical data sheet of 06/02/2014

Art. 02040220 - 02040250

of 30/10/2022

PROPERTIES	Tape 2 AC 20	Tape 2 AC 50
Article	02040220	02040250
Measurements	20 mm x 50 m	50 mm x 50 m
Colour	Transparent	
Adhesive	Solvent and emollient free acrylic based adhesive	
Adhesive backing	None	
Adhesive weight	230 g/m2 (DIN EN ISO 536)	
Reinforcement	PET mesh	
Thickness (without cover)	0,22 - 0,24 mm (DIN EN 1942)	
Covering material	Silicone liner	
Peel adhesion (AFERA 5001)	≥25 N/25mm	
Application temperature	+5 °C / +30 °C	
Operating temperature	-30 °C / +120 °C	
Resistance to condensation	High	
Resistance to aging	Very high	
Initial adhesion (*tack*)	High	
Packaging	12 rolls	5 rolls
Storage	Cool and dry away from UV rays, max. 24 months	
Storage temperature	+18 °C / +25 °C	

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com. This data sheet replaces the previous copy.